



**YOUR
SMART
ENERGY**

SMILE-G3

RESIDENTIAL SERIES

POWER

3.6 / 5 kW inverter

CAPACITY

10.1 kWh Battery modular
Expandable to 60.5 kWh



200% PV Input

Grid-Forming Function

Off-Grid Parallel Operation

Faster Response for VPP Control



SMILE-G3



Model	SMILE-G3-S3.6	SMILE-G3-S5	SMILE-G3-B5
System Specification			
Nominal Output Power	3600 W	5000 W	5000 W
Capacity Range	10.1 ~ 60.5 kWh (95% DoD)		
Battery Chemistry	LFP (LiFePO4)		
IP Protection	IP65 (Outdoor)		
System Dimension (W x D x H)	610 x 230 x 1168 mm (with Bracket)		
System Weight	109.5 kg		
Warranty	5 Year Product Warranty, 10 Year Battery Performance Warranty		
Inverter Technical Specification			
Model	SMILE-G3-S3.6-INV	SMILE-G3-S5-INV	SMILE-G3-B5-INV
Coupling	Hybrid	Hybrid	AC
Max. PV Input Power	7200 W	10000 W	NA
Max. PV Input Current	15 A / 15 A		NA
Max. PV Input Voltage	580 V		NA
MPPT Number/Max. Input Strings Number Per MPPT	2/1		NA
MPPT Voltage Range	100 ~ 550 V		NA
Max. PV Short-circuit Current	18.75 A / 18.75 A		NA
Max. Charging/Discharging Current	60 A		
Max. Charging/Discharging Power	3600 W	5000 W	5000 W
Rated Frequency	50 / 60 Hz		
Rated Voltage	230 V		
Rated output Apparent Power(Grid Port)/ Rated output Apparent Power(EPS Port)	3600 VA	5000 VA	5000 VA
Max.AC input Power(Grid Port)	7200 W	10000 W	10000 W
Rated Output Current(Grid Port)/ Max.AC Output Current(Grid Port)/ Rated Output Current(EPS Port)/ Max.AC Output Current(EPS Port)	15.6 A	21.7 A	21.7 A
Max Inverter Efficiency	96.6%		
Backup	UPS		
Communication	Ethernet / WiFi		
Humidity	0~90% (No Condensing)		
Dimension (W x D x H)	610 x 212 x 366 mm		
Weight	19.5 kg		
Safety	IEC 62109, IEC 62040		
EMC	EN61000-6-1/-2 /-3/-4		
Grid Regulation	AS4777.2, NRS 097		
Battery Technical Specification			
Module Mode	SMILE-G3-BAT-10.1P		
Module Capacity	10.1 kWh		
Usable Capacity	9.6 kWh		
Depth of Discharge (DoD)	95%		
Nominal Voltage	96 V		
Battery Voltage Range	91.5 V ~ 106.5 V		
Max. Charging/Discharging Current	60 A		
Operating Temperature Range	-10 °C ~ 50 °C*		
Cycle Life	8000**		
Battery Modules Connection	1 ~ 6 in Parallel		

* When the ambient temperature is too low or too high, the performance of battery may be limited.

** Under specific test conditions.

*** Made in China.



Headquarter: Alpha ESS Co., Ltd.

+86 513 8060 6891
 info@alpha-ess.com
 www.alpha-ess.com
 Jinhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609
 info@alpha-ess.com
 www.alpha-ess.com
 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

Australia: Alpha ESS Australia Pty. Ltd.

+61 402 500 520 (Sales)
 +61 1300 968 933 (Technical Support)
 australia@alpha-ess.com
 www.alpha-ess.com.au
 Unit 1, 2 Ralph Street Alexandria NSW 2015

Germany: Alpha ESS Europe GmbH

+49 6103 4591 601
 europe@alpha-ess.de
 www.alpha-ess.de
 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Italy: Alpha ESS Italy S.r.l.

+39 599 239 50
 info@alpha-ess.it
 www.alpha-ess.it
 Via Loda, 17-41013 Castelfranco Emilia (MO)

Korea: Alpha ESS Korea Co., Ltd.

+82 64 721 2004
 korea@alpha-ess.com
 www.alpha-ess.com
 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

USA: Alpha ESS USA, Inc.

USA@alpha-ess.com
 638 S Ahwanee Ter Sunnyvale, California, 94085 United States of America

UK: Alpha ESS UK Ltd.

uk@alpha-ess.com
 Drake House, Long Street, Dursley, gl11 4hh

Singapore: Alpha ESS International Pte. Ltd.

Singapore@alpha-ess.com
 2 Corporation Road #01-06A Corporation Place Singapore 618494